Haier Display

HV-720TS Specification

Bezel color options	silver/black, silver/grey, silver/silver, black/black, beige color, ivory white
TFT panel	LG.PHILIPS/Hannstar/CPT/BOE
Speaker	with
Dot pitch (mm)	0.264
View angel	H:+80 / -80; V: +70 / -70
Resolution (maximum/best)	1280x1024@75Hz/1280x1024@60Hz
Max contrast ratio:	500 : 1
Max brightness:	300cd/m
Response time tr/tf:	12ms
Color:	16.7M
Input signal:	Analog
Input DVI:	+USD4
Control manner	OSD
Logo on front	Logo plate or silk screen
Power consumption operating/suspend/off	<40W/ <5W/<3W
Power supply	AC100-240V 60/50Hz, 1.5A, 12V DC, 4.2A
Operating temperature	5~40 centi degree
Operating humidity	20% -80%
Storage temperature	-20~45 centi degree
Storage humidity	10% -90%
Certificate	TCO99,CE,FCC,CB,ISO9001
Packing carton size (mm):	455X165X440
Weight (kg)	NW: 5.0; GW: 7.0
Container load w/o pallet (MOQ)	840pcs/20' ;1820/40' ; 2182pcs/40'HQ
Container load with pallet (MOQ)	840pcs/20' ;1680ps/40'; 1680pcs/40'HQ